PRODUCT DATA SHEET



PRODUCT CODES

RANGE

Laminate Panels

DESCRIPTION

The Original, Impression and Majestic Collections

CARE & MAINTENANCE

DO	Regularly use non-abrasive cleaner to clean the panels.
	Replace any exposed silicone sealant periodically, or as necessary, to ensure a continual waterproof seal.
	Rinse your Burlington panels down after use as a multitude of various chemicals can be present within personal hygiene products used in bathrooms. Rinsing these off, avoids issues such as sealant discolouration.
	Ensure adequate ventilation is present when using your shower or bath to avoid mould and mildew growth occurring.
DON'T	Use any form of abrasive cleaner as these may result in dulling of your panel surface and accelerated wear affects.
	Use any form of bleach product to clean your Burlington panels as harsh chemicals contained in bleaches can affect the surface of your panel

	DIMENSIONS	WATERPROOF CORE PANEL WEIGHT
SQUARE CUT PANEL SIZE	2440 x 900 x 10.5mm	20kg
SQUARE CUT PANEL SIZE	2440 x 1200 x 10.5mm	27kg
PROCLICK PANELS	2440 x 579 x 10.5mm	13kg
PROCLICK PANELS	2440 x 879 x 10.5mm	20kg
PROCLICK PANELS	2440 x 1179 x 10.5mm	27kg

DIMENSION TOLERANCE

WIDTH	+/- 3.0mm
HEIGHT	+/- 5.0mm
THICKNESS	+/- 0.5mm
FLATNESS	≤3mm/m
SQUARENESS	+/- 1.5mm per 1000mm

MATERIAL

Face laminates are produced to EN 438 standard (VGS) and are bonded to a quality exterior grade MDF, or Plywood using a D3 adhesive applied under strictly controlled conditions. A balancing backing laminate is then bonded to the panel reverse.

FIRE RATINGS / PERFORMANCE

All Burlington laminate panels are classified EN 13501. In addition, selected decors are British Standard Fire Rated Class 2-BS 476: Part 7: 1997. Please check with your Burlington supplier or retailer for confirmation of any particular decors F.R status prior to purchase, if required.

GUARANTEE

30 year warranty against manufacturing defects in a domestic environment (subject to installation registration), and 5 years when installed in a commercial environment.

DISCLAIMER

Be aware that gloss finished decors have a lower scratch resistance than textured decors and that the stated care & maintenance procedures must be followed to minimise normal wear and tear of the products.

and sealant.

